



Catalog of Fan coil unit

Floor Standing Fan Coil Unit (LM Series)

Specification:

- Air flow: 340-2380m³/h
- Cooling capacity: 1800W-12600W
- Heating capacity: 2700W-18900W
- The thickness of the unit is 260mm
- With Led display thermostat
- Europe/American/British plugs are available

Detail Pictures:



Catalog of Fan coil unit

Many Plugs available:

1



American plug

2



Chinese plug

3



European plug

4



British plug

Controller on the device:





Catalog of Fan coil unit

Data table:

Specification		FP-34 LM	FP-51 LM	FP-68 LM	FP-85 LM	FP-102 LM	FP-136 LM	FP-170 LM	FP-204 LM	FP-238 LM
nominal air volume (m³/h)	High	340	510	680	850	1020	1360	1700	2040	2380
	middle	260	390	520	650	780	1040	1290	1580	1820
	Low	180	270	360	450	530	710	890	1060	1240
Cooling capacity (w)	High	1800	2700	3600	4500	5400	7200	9000	10800	12600
	Middle	1620	2450	3240	4050	4850	6480	7980	9580	11200
	Low	1430	1990	2650	3220	3820	5140	6400	7480	8960
Heating capacity (w)	High	2700	4050	5400	6750	8100	10800	13500	16200	18900
	Middle	2450	3680	4860	6120	7275	9980	11960	14200	16520
	Low	2160	3240	4300	5200	6400	8600	9200	10800	12960
Input power	Standard type	41	54	65	82	98	132	168	206	247
(w)	Overpressure type	45	58	76	89	110	165	195	228	273
Outlet static press of unit(Pa)		12Pa,30Pa,50Pa								
Electric power		Signal phase 220v 50HZ								
Heat exchanger	Model	3-row aluminum								
	Structure model	copper stringing roll aluminum fin								
	working pressure	1.2Mpa								
	water pipe branching	DN20 pipe								
	condensed water connecting hose	DN20 pipe								
water volume (kg/h)		350	480	680	780	910	1140	1270	1320	1460